



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SDR-104 SERIES

PART NO.	INDUCTANCE (uH)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SDR-104-100 □	10	2.52M	0.053	2.38
SDR-104-120 □	12	2.52M	0.061	2.13
SDR-104-150 □	15	2.52M	0.070	1.87
SDR-104-180 □	18	2.52M	0.081	1.73
SDR-104-220 □	22	2.52M	0.088	1.60
SDR-104-270 □	27	2.52M	0.100	1.44
SDR-104-330 □	33	2.52M	0.120	1.26
SDR-104-390 □	39	2.52M	0.151	1.20
SDR-104-470 □	47	2.52M	0.170	1.10
SDR-104-560 □	56	2.52M	0.199	1.01
SDR-104-680 □	68	2.52M	0.223	0.91
SDR-104-820 □	82	2.52M	0.252	0.85
SDR-104-101 □	100	1.00K	0.344	0.74
SDR-104-121 □	120	1.00K	0.396	0.69
SDR-104-151 □	150	1.00K	0.544	0.61
SDR-104-181 □	180	1.00K	0.621	0.56
SDR-104-221 □	220	1.00K	0.721	0.53
SDR-104-271 □	270	1.00K	0.949	0.45
SDR-104-331 □	330	1.00K	1.100	0.42
SDR-104-391 □	390	1.00K	1.245	0.38
SDR-104-471 □	470	1.00K	1.526	0.35
SDR-104-561 □	560	1.00K	1.904	0.32
SDR-104-681 □	680	1.00K	2.100	0.18
SDR-104-821 □	820	1.00K	2.400	0.165
SDR-104-102 □	1000	1.00K	2.700	0.150

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME