

SMT POWER INDUCTORS (SDS075D/125D/126D/128D)

Various high power inductors are superior to be high saturation for surface mounting.

Applications: Power supply for VTR, OA equipment, LCD television set, notebook PC, portable communication equipment DC/DC converters etc.

PRODUCT IDENTIFICATION

SD- SDS-□□□-□□□-□

1. 2. 3. 4. 5.

(1) MODEL


(2) SERIES

(3) SIZE



(4) INDUCTANCE

(5) TOLERANCE (J:±5%, K:±10%, E:±15%, M:±20%, T:±30%)

CONFIGURATIONS & DIMENSIONS



TOP VIEW



BOTTOM VIEW

TYPE	A	B	ΦC	D	E	F
SDS-075D	7.2±0.3	7.2±0.3	4.5(max)	2.5±0.2	2.5±0.3	5.6±0.2
SDS-125D	12±0.3	12±0.3	4.6(max)	5.0±0.2	6.0±0.3	10±0.2
SDS-126D	12±0.3	12±0.3	6.0(max)	5.0±0.2	6.0±0.3	10±0.2
SDS-128D	12±0.3	12±0.3	8.0(max)	5.0±0.2	6.0±0.3	10±0.2

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME