



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SDO1608 SERIES

PART NO.	INDUCTANCE (uH)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SDO-1608-1R0 ☐	1.0	100K	0.05	2.90
SDO-1608-1R5 ☐	1.5	100K	0.05	2.60
SDO-1608-2R2 ☐	2.2	100K	0.07	2.30
SDO-1608-3R3 ☐	3.3	100K	0.08	2.00
SDO-1608-4R7 ☐	4.7	100K	0.09	1.50
SDO-1608-6R8 ☐	6.8	100K	0.13	1.20
SDO-1608-100 ☐	10	100K	0.16	1.10
SDO-1608-150 ☐	15	100K	0.23	0.90
SDO-1608-220 ☐	22	100K	0.37	0.70
SDO-1608-330 ☐	33	100K	0.51	0.58
SDO-1608-470 ☐	47	100K	0.64	0.50
SDO-1608-680 ☐	68	100K	0.86	0.40
SDO-1608-101 ☐	100	100K	1.27	0.31
SDO-1608-151 ☐	150	100K	2.00	0.27
SDO-1608-221 ☐	220	100K	2.65	0.22
SDO-1608-331 ☐	330	100K	3.80	0.18
SDO-1608-471 ☐	470	100K	5.06	0.16
SDO-1608-681 ☐	680	100K	9.20	0.14
SDO-1608-102 ☐	1000	100K	13.80	0.10

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME