



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SDO-3316 SERIES

PART NO.	INDUCTANCE (uH)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SDO-3316-1R0 □	1.0	100K	0.009	9.00
SDO-3316-1R5 □	1.5	100K	0.010	8.00
SDO-3316-2R2 □	2.2	100K	0.012	7.00
SDO-3316-3R3 □	3.3	100K	0.015	6.40
SDO-3316-4R7 □	4.7	100K	0.018	5.40
SDO-3316-6R8 □	6.8	100K	0.027	4.60
SDO-3316-100 □	10	100K	0.038	3.80
SDO-3316-150 □	15	100K	0.046	3.00
SDO-3316-220 □	22	100K	0.085	2.60
SDO-3316-330 □	33	100K	0.100	2.00
SDO-3316-470 □	47	100K	0.140	1.60
SDO-3316-680 □	68	100K	0.200	1.40
SDO-3316-101 □	100	100K	0.280	1.20
SDO-3316-151 □	150	100K	0.400	1.00
SDO-3316-221 □	220	100K	0.610	0.80
SDO-3316-331 □	330	100K	1.020	0.60
SDO-3316-471 □	470	100K	1.270	0.50
SDO-3316-681 □	680	100K	2.020	0.40
SDO-3316-102 □	1000	100K	3.000	0.30
SDO-3316-152 □	1500	100K	6.000	0.11
SDO-3316-103 □	10000	100K	33.00	0.075

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME