



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SDOS-1608 SERIES

PART NO.	INDUCTANCE (uH)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SDOS-1608-1R0 □	1.0	30K	0.040	3.00
SDOS-1608-1R5 □	1.5	30K	0.045	2.80
SDOS-1608-2R2 □	2.2	40K	0.050	1.80
SDOS-1608-3R3 □	3.3	40K	0.055	1.60
SDOS-1608-4R7 □	4.7	40K	0.060	1.40
SDOS-1608-6R8 □	6.8	40K	0.065	1.20
SDOS-1608-100 □	10	40K	0.075	1.00
SDOS-1608-150 □	15	40K	0.090	0.80
SDOS-1608-220 □	22	40K	0.110	0.70
SDOS-1608-330 □	33	40K	0.190	0.60
SDOS-1608-470 □	47	40K	0.230	0.50
SDOS-1608-680 □	68	40K	0.290	0.40
SDOS-1608-101 □	100	40K	0.480	0.30
SDOS-1608-151 □	150	40K	0.590	0.26
SDOS-1608-221 □	220	40K	0.770	0.22
SDOS-1608-331 □	330	40K	1.400	0.20
SDOS-1608-471 □	470	40K	1.800	0.19
SDOS-1608-681 □	680	40K	2.200	0.18
SDOS-1608-102 □	1000	40K	3.400	0.15
SDOS-1608-152 □	1500	50K	4.200	0.12
SDOS-1608-222 □	2200	50K	8.500	0.10
SDOS-1608-332 □	3300	50K	11.00	0.08
SDOS-1608-472 □	4700	50K	13.90	0.06
SDOS-1608-682 □	6800	50K	25.00	0.04
SDOS-1608-103 □	10000	50K	32.80	0.02

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME