



SMT CERAMIC INDUCTORS
ELECTRICAL CHARACTERISTICS FOR SCM-0805 SERIES

PART NO	INDUCTANCE (nH/uH)	Q Min	F(MHz)		SRF(MHz) (min)	RDC(Ω) (max)	IDC(mA) (max)
			L	Q			
SCM-0805-2N2 □	2.2nH	15	250	1500	6000	0.08	600
SCM-0805-3N3 □	3.3nH	50	250	1500	6000	0.08	600
SCM-0805-6N8 □	6.8nH	50	250	1000	5500	0.11	600
SCM-0805-8N2 □	8.2nH	50	250	500	4700	0.12	600
SCM-0805-12N □	12nH	50	250	500	4000	0.15	600
SCM-0805-15N □	15nH	50	250	500	3400	0.17	600
SCM-0805-18N □	18nH	50	250	500	3300	0.20	600
SCM-0805-22N □	22nH	55	250	500	2600	0.22	500
SCM-0805-27N □	27nH	55	250	500	2500	0.25	500
SCM-0805-33N □	33nH	60	250	500	2050	0.27	500
SCM-0805-39N □	39nH	60	250	500	2000	0.29	500
SCM-0805-47N □	47nH	60	200	500	1650	0.31	500
SCM-0805-56N □	56nH	60	200	500	1550	0.34	500
SCM-0805-68N □	68nH	60	200	500	1450	0.38	500
SCM-0805-82N □	82nH	65	150	500	1300	0.42	400
SCM-0805-R10 □	0.10uH	65	150	500	1200	0.46	400
SCM-0805-R12 □	0.12uH	50	150	250	1100	0.51	400
SCM-0805-R15 □	0.15uH	50	100	250	920	0.56	400
SCM-0805-R18 □	0.18uH	50	100	250	870	0.64	400
SCM-0805-R22 □	0.22uH	50	100	250	850	0.70	400
SCM-0805-R27 □	0.27uH	40	100	100	800	1.10	280
SCM-0805-R33 □	0.33uH	40	100	100	750	1.20	260
SCM-0805-R39 □	0.39uH	40	100	100	700	1.50	200
SCM-0805-R47 □	0.47uH	40	100	100	650	2.50	170
SCM-0805-R56 □	0.56uH	40	50	50	600	3.50	170
SCM-0805-R68 □	0.68uH	30	50	50	550	4.00	170

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME