



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SDR-105 SERIES

PART NO.	INDUCTANCE (uH)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SDR-105-100 □	10	2.52M	0.060	2.60
SDR-105-120 □	12	2.52M	0.070	2.45
SDR-105-150 □	15	2.52M	0.080	2.27
SDR-105-180 □	18	2.52M	0.090	2.15
SDR-105-220 □	22	2.52M	0.100	1.95
SDR-105-270 □	27	2.52M	0.110	1.76
SDR-105-330 □	33	2.52M	0.120	1.50
SDR-105-390 □	39	2.52M	0.140	1.37
SDR-105-470 □	47	2.52M	0.170	1.28
SDR-105-560 □	56	2.52M	0.190	1.17
SDR-105-680 □	68	2.52M	0.220	1.11
SDR-105-820 □	82	2.52M	0.250	1.00
SDR-105-101 □	100	1.00K	0.350	0.97
SDR-105-121 □	120	1.00K	0.400	0.89
SDR-105-151 □	150	1.00K	0.470	0.78
SDR-105-181 □	180	1.00K	0.630	0.72
SDR-105-221 □	220	1.00K	0.730	0.66
SDR-105-271 □	270	1.00K	0.970	0.57
SDR-105-331 □	330	1.00K	1.150	0.52
SDR-105-391 □	390	1.00K	1.300	0.48
SDR-105-471 □	470	1.00K	1.480	0.42
SDR-105-561 □	560	1.00K	1.900	0.33
SDR-105-681 □	680	1.00K	2.250	0.28
SDR-105-821 □	820	1.00K	2.550	0.24
SDR-105-102 □	1000	1.00K	2.600	0.20

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME