



SMT POWER INDUCTORS

ELECTRICAL CHARACTERISTICS FOR SI453226 SERIES

PART NO.	INDUCTANCE (uH)	TEST FREQ (Hz)	RDC(Ω) (max)	IDC(A) (max)
SI-453226-1R0 □	1.00	1M	0.08	1.08
SI-453226-1R5 □	1.50	1M	0.09	1.00
SI-453226-2R2 □	2.20	1M	0.11	0.90
SI-453226-3R3 □	3.30	1M	0.13	0.80
SI-453226-4R7 □	4.70	1M	0.15	0.75
SI-453226-6R8 □	6.80	1M	0.20	0.72
SI-453226-100 □	10	1M	0.24	0.65
SI-453226-150 □	15	1M	0.32	0.57
SI-453226-220 □	22	1M	0.60	0.42
SI-453226-330 □	33	1M	1.00	0.31
SI-453226-470 □	47	1M	1.10	0.28
SI-453226-680 □	68	1M	1.70	0.22
SI-453226-101 □	100	1M	2.20	0.19
SI-453226-151 □	150	1M	3.50	0.13
SI-453226-221 □	220	1M	4.00	0.11
SI-453226-331 □	330	1M	6.80	0.10
SI-453226-471 □	470	1K	8.50	0.09
SI-453226-561 □	560	1K	9.00	0.07
SI-453226-681 □	680	1K	13.00	0.06
SI-453226-821 □	820	1K	15.00	0.05
SI-453226-102 □	1000	1K	25.00	0.045

歡迎客戶提供規格 CUSTOMER SPECIFICATION IS WELCOME